

CLF Range

| | CLF511 | CL4.4 | CL8.4 | CLF532 | CLF564 | CL55H |
|----------------------|---|------------------------------------|------------------------------------|----------------------------|----------------------------|--------------------------------------|
| Rated Power: | 80w | 120w | 240w | 250w | 450W | 400w |
| Nominal Impedance: | 8Ω | 8Ω | 8Ω | 8Ω | 8Ω | 8Ω |
| SPL (1w1m): | 88dB | 97dB | 100dB | 94dB | 102dB | 102dB |
| Max SPL: | 107dB | 118dB | 123dB | 118dB | 128dB | 128dB |
| Frequency response: | 67Hz - 20KHz | 125Hz - 20KHz | 125Hz - 90KHz | 65Hz - 20KHz | 60Hz - 20KHz | 67 - 20KHz |
| Component: | 1 x 5" Woofer, 1 x 0.5" HF | 4 x 4" (0.75" coil) Ferrite Woofer | 8 x 4" (0.75" Coil) Ferrite Woofer | 3 x 5" Woofer, 2 x 0.5" HF | 6 x 5" Woofer, 4 x 0.5" HF | 5 x 5" Woofer, 1 x 1" HF Compression |
| Enclosure: | 9mm Birch Ply | 12mm Birch Ply | | | | |
| IP Rating: | IP20 | | | | | |
| Finish: | Black, White or Custom Colour | | | | | |
| Flying Points | 2 x M8 Fixings | 2 x M10 Fixings | | 7 x M10 Fixings | | 3 x M10 Fixings |
| | APT-CLF511B Bracket (included) | Powerdrive 75 point | | | | |
| Pole Mount: | N/A | M20 Pole Mount | | | | 35mm Top hat with M20 Thread |
| Speaker Connections: | 2 x Neutrik Speakon NL4, 4mm Binding posts or 4 pole Euro block connector | | | | | |
| Weight: | 2Kg | 8Kg | 12Kg | 6Kg | 13Kg | 12Kg |
| Size (HWD): | 225, 150, 155mm | 495, 150, 155mm | 940, 150, 1555mm | 535, 165, 155mm | 1000, 165, 155mm | 1000, 168, 178mm |
| Amplifier Power: | 125w RMS | 350w RMS | 700w RMS | 400w RMS | 600w RMS | 600w RMS |

