




Apt-CLF55H Specification Sheet.

Image

Dimensions (HWD):

Dimensions

1000, 168, 176mm






Recommended Settings & Accessory

Crossover settings:	70Hz BW 48dB	
With SC18.1	100Hz 24dB LR	
With SC12.2	125Hz 24dB LR	
Amplifier:	600w RMS	
Recommended Sub:	APT-SC18.1, SC12.2	

Specification:

Rated Power (AES)	400w
Rated impedance:	8Ω
SPL (1w1m)	102dB
SPL max:	128dB
Frequency response:	67Hz - 20KHz
Component:	5 x 5" (1.26" coil) Driver
	1 x 1" HF Compression Driver
Dispersion angle:	90° x 60°
IP rating:	IP20
Enclosure:	12mm Birch ply
Finish:	Black, White or *Custom colour
Flying points:	3 x M10 Fixings, Powerdrive 75 Point
	35mm Top hat with M20 Thread
Connector:	2x Neutrik Speakons
Weight:	12Kg

Frequency Response



Tel: +44 (0) 1579 212210 Email: info@apt-gb.com Website: www.apt-gb.com

^{*} Custom paint colours may incur extra cost and increase build time.
** Binding Post, 4 Pole euro block connector available may increase build time.
Feet are not supplied on all cabins that have locations on them
Specification can be changed by APT-GB with out prior notice.
Apt-GB is trading as part of the GGPM LTD Group.